



SECTION 1: DESCRIPTION & BENEFITS

- 90-micron kraft paper backing
- Single sided laminate with PET film or other chemical film
- Coated with instant high tack rubber/resin adhesive
- Easy hand-tear for easy application & printable
- Easy degradation, no pollution to environment
- High conformability & tensile strength
- Ideal vapor and moisture barrier



SECTION 2: SPECIFICATIONS

Product Characteristics	Performance Data	Test Method
Kraft Paper Thickness	90 microns (3.6 mil)	PSTC-133/ASTM D3652
Total Thickness	120 microns (4.8 mil)	PSTC-133/ASTM D3652
Peel Adhesion	12 N/25mm (43.2 Oz/In)	PSTC-101/ASTM D3330
Rolling Ball Tack	5 cm (2.0 Inch)	PSTC-6/ASTM D3121
Static Shear (Room Temp.)	≥ 12 Hours	PSTC-107/ASTM D3654
Tensile Strength	50 N/25mm (11.4 Lb/In)	PSTC-131/ASTM D3759
Elongation at Break	9.0%	PSTC-131/ASTM D3759
Service Temp.	-15 ~ +80°C (+23 ~ +176 °F)	
Operating Temp.	0 ~ +40°C (+32 ~ +104 °F)	

SECTION 3: APPLICATIONS & OTHER DETAILS

- Carton sealing
- Wiring harness bundling, plastic parts fixing, leaking stoppage for white goods applications
- General purpose like: protecting, sealing, masking, attaching etc.



Sliced roll width available (or customized): 38,48,50,72,75,96,100 mm, etc.

Length: 50, 100m, etc.

Tolerance: Thickness: +/- 10% Width: +/-1.0mm Length: +/- 0.4m

Storage: Indoor storage: -5°C-40°C(humidity: <80% =, cool & dry, free of direct sunlight

Shelf Life: 12 months in room temp.

N.B. Please keep the operating surface clean, dry, and free of grease or other dirt. So that **Egret Tape** can have a best performance.

Changzhou Egret Manufacturing Co., Ltd

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807 Email: info@egretmfg.com Website: www.egretmfg.com